

TECHNICAL SPECIFICATIONS (3/3)

FEATURES

Auto & Manual Focus	Picture flip	Image format
Iris, Gain & Exposure Time	Start and lock magnification	Auto capture mode and interval
Snapshot	Closeup Lenses	System units
Presets	Date and time	Focus stacking
White balance calibration	Ruler on/off and choose ruler color	Laser pointer
Turn light on/off	Monitor width or Monitor Auto Detect	Measurement Application (TMA) (Optional)

LENS

Dimensions	58 mm/2.3"
Included lens	+4

LENSES

	Lens to object distance	Magnification on 22" monitor
+3	333 mm/13.1"	1.2x - 35.4x
+4	250 mm/9.8"	1.6x - 47.3x
+5	200 mm/7.9"	1.9x - 59.3x
+10	100mm/3.9"	3.8x - 115.5x
+25	34mm/1.34"	9.6x - 297.1x

RECOMMENDED MONITOR FORMAT

Panel format	16:9 (Widescreen)
How to link	DVI or HDMI input
Response time	2 ms
Signal format	FHD 1920x1080

ACCESSORIES

Lens, +3, +4, +5, +10, +25	FHD monitor 22" and 24	Flexarm
XPLUS FHD Control box	Mounting arm for monitor	Cleaning kit
XKEY Control box	Table and wall mount for monitor arm	Dust cover
Foot switch	Circular tilting table	Coaxial light
Ring light kit	Height Adjustment Table	
Ultra Violet ring light	XY-Table	
Infrared ring light	Backlight kit	