

XSD Series

Fast reset & drying



Perfection
down to the last detail

XSD SERIES

HIGH END TECHNOLOGY




Smart Connect
XSD(B) Series cabinets are ready to be connected within a network.

THE FASTEST DRYING CABINETS

XSD Series high-end desiccant dry cabinets are designed to exceed the formidable challenges associated with IPC/JEDEC J-STD-033 and 1601 for handling Moisture Sensitive Devices. The advanced technology of XSD desiccant cabinets delivers a process combining ultra low humidity (<0.5%) and mild temperatures (40-60°C) for floor life reset proven to replace traditional oven baking of components and boards at a fraction of the cost.



FEATURES	XSD(B) 701-55	XSD(B) 701-55-S	XSD(B) 1412-55	XSD(B) 1412-55-S
10" Touchscreen display	✓	✓	✓	✓
MSL Software license	X	✓	✓	✓
Handscanner	X	✓	X	✓
Personal Computer	X	✓	X	✓
Pick by light license	✓	✓	✓	✓
Smart Reel Rack	✓	✓	✓	✓
Standard Reel Rack	✓	✓	✓	✓
Smart Connect	✓	✓	✓	✓



Smart reel rack
Component wet ●
Reset active ●
Reset completed ●

Pick by Light

Find what you are looking for
The MSL software has the option to integrate Pick by Light solutions, which will allow visual indication of storage locations during 'store-in' and 'take out'.

LED statuses when idle
During normal operation (idle), pick by light can optionally actively visualise the status of the location with colours. This function can be enabled or disabled within the MSL software.


Volume optimized XSD SERIES:
XSD(B) 1412: 330-360 mm X 8 mm 296 reels per cabinet.
XSD(B) 701: 330-360 mm X 8 mm 148 reels per cabinet.

Characteristics

- U-5000 series dryer:** Air drying to below 0.5% RH
Regeneration: dynamic
- Sensor:** Integrated Rotronic sensor, accuracy +/- 0.8% RH and +/- 0.2°C
- Performance:** 6 min. recovery time after door opening to below 1% RH
- Control:** Limit value settings through display or web interface
Door and humidity alarm function
- Climate control:** Standard heating up to 40 - 60 °C
- Documentation:** Integrated data logger
Climate data recording
Free Totech Viewer software

Smart Connect Cabinets


Storage & MSL Management on many levels



MSL Software

The MSL 2.5 software enables manufacturers of any size to comprehensively maintain control of all their component inventory and particularly their moisture sensitive devices. Whether integrated with existing

ERP and MES systems or used in a standalone fashion, real time monitoring and traceability of moisture sensitive inventory helps manufacturers on the path to achieving their industry 4.0 goals.



Totech Europe BV
Paxtonstraat 11
8013 RP Zwolle
The Netherlands

Phone.: +31 (0) 38 20 3 1051
Fax: +31 (0) 38 2203 1052
sales@totech.eu
www.totech.eu

TOTECH
A Member of the ASYS Group