

7175



Product Description

7175 is a polyimide film, anti-static (ESD) treated, single-coated tape with silicone adhesive.

Performance Features

Dimensionally stable at high temperatures.
Flame retardent and chemical resistant.
Excellent heat, cold, solvent and voltage resistance.
Designed to minimize static effect during stripping and peeling.

Applications

Serves as a mask for printed circuit boards during wave solder or solder dip process.
Protects specific areas of a PCB.

Technical information

	Values	Tolerance	Test Method
Adhesive	Silicone		
Backing Thickness (mm)	0,025	0.023-0.029	ASTM D3652
Adhesive Thickness (mm)	0,04	0.037-0.045	ASTM D3652
Total Thickness (mm)	0,065	0.06-0.071	ASTM D3652
Adhesion to Steel (N/25mm)	6	5.39-6.47	ASTM D3330
Tensile Strength (N/25mm)	122,57	> 102.96	ASTM D3759
Elongation (%)	63	45 - 80	ASTM D3759
Insulation Class (°C)	180	200	
Dielectric Breakdown (kV)	6	> 5	ASTM D149
Colour	Amber		

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.

The values noted in above technical specification are given only for customers' reference and should not be used in writing specifications.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com